


Ø12.7±0.1

CUT-OUT



Panel Thickness: 3mm MAX.

Rating: 3A 125V AC ;  
 1.5A 250V AC ;  
 Contact Resistance: 50mΩ Max. ;  
 Insulation Resistance:DC 500V 100MΩ Min. ;  
 Dielectric Strength:AC 1000V 1 minute  
 Total Travel: 2.0±0.4mm  
 Operating Force:150±100gf  
 Operating Life:10,000 cycles  
 Mechanical Life:50,000 cycles Min. ;  
 Operating Temperature:0°C~85°C  
 Function: OFF-(ON)

**MATERIAL**

Base: PA66, UL rated :94V-2 Min. ;  
 Cap: ABS ;  
 Terminal: Copper, Silver or Tin plated ;  
 Nut: Brass, Ni plated.

Y	Yellow
W	White
U	Blue
R	Red
O	Orange
G	Green
B	Black
A	Gray
CAP COLOR (X)	

REVISION	DESCRIPTION	REVISED BY	TOLERANCES .X±0.3 .XX±0.15 ANGLE ±1°			UNIT	mm	PART NAME	PB SPEC DRAWING	DWG NO
△			DRAWN BY		DESIGNED BY		SCALE			
△			CHECKED BY		APPROVED BY		DATE	2010.05.05	PART NO	
△	2013.05.06		修改端子间距							
△	2010.05.05		换新图框,重新出图							